

JFB

JFB Hart Coatings, Inc.



MatteTek™

Premium, Ultra Durable Floor Finish

Costs Savings:	Reduces floor care costs on average 45% or more
Less Disruptions:	Floors don't need to be burnished or stripped
High Performance:	Outperforms alternative products in virtually every category
Environmental:	No odor, low VOCs (< 50 g/l)
Abrasion Resistance:	Maintains gloss level
UV Resistant:	WILL NOT yellow!
Slip Co-Efficient:	Increased slip resistance

MatteTek™ is available with Adhesion Plus™, GripLok™ and GripLok Gloss™

MatteTek™

Technical Specifications

Gloss @ 60° Angle:	MatteTek: Up to 20°
Weight Gallon:	8.85 lbs./gallon kit
	Combined Parts A, B & C
Catalyze Ratio:	As supplied in pre-measured kit
Weight Solids:	49% ±3% Catalyzed and Reduced
Volume Solids:	47% ±3% Catalyzed and Reduced
Flashpoint:	> 200° F
VOCs:	< 15 g/l
Adhesion (ASTM D3359):	Average results 5B (0% removed)
Abrasion (ASTM D4060):	33 mg loss
Hardness (ASTM D3363):	Gouge: 2H; Scratch H
Chemical Resistance: MEK – double rubs	> 200 double rubs
Application Viscosity:	65 – 75 KU Catalyzed and Reduced
Application Conditions:	Up to 80% Relative Humidity 40° – 95° F Air and Surface Temperature
Recommended Film Thickness:	Wet: 2 – 4 mils Dry: 1 – 2 mils
Actual Spread Rate:	Approximately 300 square feet per gallon, per coat
Pot Life:	60 minutes
Dry Time:	8 hours
Shelf Life:	1 year (12 months)
Recommended Coats:	One or two, depends on performance requirements and substrate profile
Clean-Up:	Water, or you may use a mixture of water and a small amount of ammonia
Application Substrates:	VCT, Vinyl Sheeting, Luxury Vinyl Tile, Asbestos Tile, Synthetic Wood Vinyl, Ceramic, Quarry Tile, Wood, Concrete, Terrazzo, Linoleum and Poured Urethane Floors



GlossTek™



GlossTek Fast Dry™



SatinTek™



MatteTek™



VersaTek™

GlossTek Additives:

- ◆ Adhesion Plus
- ◆ GripLok
- ◆ GripLok Gloss

JFB Hart Coatings, Inc.

10210 Werch Drive – Suite 203
Woodridge, Illinois 60517

www.jfbhartcoatings.com

630-633-6228 ♦ 630-633-6238 fax

Revised: March 2011

