

# JFB

JFB Hart Coatings, Inc.



## SatinTek™

**Premium, Ultra Durable Floor Finish**

<b>Costs Savings:</b>	Reduces floor care costs from 30-80%
<b>Less Disruptions:</b>	Floors don't need to be burnished or stripped
<b>High Performance:</b>	Outperforms alternative products in virtually every category
<b>Environmental:</b>	No odor, low VOCs (<15 g/l)
<b>Abrasion Resistance:</b>	Maintains gloss level
<b>UV Resistant:</b>	WILL NOT yellow!
<b>Slip Co-Efficient:</b>	Increased slip resistance

SatinTek™ is available with Adhesion Plus™, GripLok™ and GripLok Gloss™

# SatinTek™

## Technical Specifications

<b>Gloss @ 60° Angle:</b>	SatinTek: Up to 50°
<b>Weight Gallon:</b>	8.85 lbs./gallon kit
	Combined Parts A, B & C
<b>Catalyze Ratio:</b>	As supplied in pre-measured kit
<b>Weight Solids:</b>	49% ±3% Catalyzed and Reduced
<b>Volume Solids:</b>	47% ±3% Catalyzed and Reduced
<b>Flashpoint:</b>	> 200° F
<b>VOCs:</b>	< 15 g/l
<b>Adhesion (ASTM D3359):</b>	Average results 5B (0% removed)
<b>Abrasion (ASTM D4060):</b>	33 mg loss
<b>Hardness (ASTM D3363):</b>	Gouge: 2H; Scratch H
<b>Chemical Resistance:</b> MEK – double rubs	> 200 double rubs
<b>Application Viscosity:</b>	65 – 75 KU Catalyzed and Reduced
<b>Application Conditions:</b>	Up to 80% Relative Humidity 40° – 95° F Air and Surface Temperature
<b>Recommended Film Thickness:</b>	Wet: 2 – 4 mils Dry: 1 – 2 mils
<b>Actual Spread Rate:</b>	Approximately 300 square feet per gallon, per coat
<b>Pot Life:</b>	60 minutes
<b>Dry Time:</b>	8 hours
<b>Shelf Life:</b>	1 year (12 months)
<b>Recommended Coats:</b>	One or two, depends on performance requirements and substrate profile
<b>Clean-Up:</b>	Water, or you may use a mixture of water and a small amount of ammonia
<b>Application Substrates:</b>	VCT, Vinyl Sheeting, Luxury Vinyl Tile, Asbestos Tile, Synthetic Wood Vinyl, Ceramic, Quarry Tile, Wood, Concrete, Terrazzo, Linoleum and Poured Urethane Floors



GlossTek™



GlossTek Fast Dry™



SatinTek™



MatteTek™



VersaTek™

### **GlossTek Additives:**

- ◆ Adhesion Plus
- ◆ GripLok
- ◆ GripLok Gloss

### **JFB Hart Coatings, Inc.**

10210 Werch Drive – Suite 203  
Woodridge, Illinois 60517

[www.jfbhartcoatings.com](http://www.jfbhartcoatings.com)

630-633-6228 ◆ 630-633-6238 fax

Revised: March 2011

